


K-WIRES + STEINMANN PINS



K-Wires

6-packs only. To order non-sterile, add "NS" to the end of the product number (e.g. 1600-XXXNS)

Length	Point Style	Type	Wire Diameter				
			0.7 mm / .028"	0.9 mm / .035"	1.1 mm / .045"	1.4 mm / .054"	1.6 mm / .062"
4"	Single Trocar	Smooth	1604-128	1604-135	1604-145	1604-154	1604-162
		Double Trocar	Smooth	1600-428	1600-435	1600-445	1600-454
		Threaded		1600-435T	1600-445T	1600-454T	1600-462T
6"	Double Trocar	Smooth	1600-628	1600-635	1600-645	1600-654	1600-662
		Threaded		1600-635T	1600-645T	1600-654T	1600-662T
9"	Single Trocar	Smooth		1600-9355	1600-9455	1600-9545	1600-9625
		Double Trocar	Smooth		1600-935	1600-945	1600-954
		Threaded		1600-935T	1600-945T	1600-954T	1600-962T



K-Wires with Wire Guide


MicroAire®

Pencil Grip Wire Driver

Models 1620, 1625, 1995 and 2600
6-packs only

Length	Point Style	Type	Wire Diameter				
			0.7 mm / .028"	0.9 mm / .035"	1.1 mm / .045"	1.4 mm / .054"	1.6 mm / .062"
5.5"	Double Trocar	Smooth	1600-020	1600-021	1600-022		1600-023
			1600-001NS	1600-002NS	1600-003NS		1600-004NS
		Wire Guide only (non-sterile) Color	1600-009NS Red	1600-010NS Blue	1600-011NS Yellow	1600-013NS White	1600-012NS Black





Steinmann Pins

6-packs only. To order non-sterile, add "NS" to the end of the product number (e.g. 1600-XXXNS)

Length	Point Style	Type	Wire Diameter						
			2.0 mm / 5/64"	2.4 mm / 3/32"	2.8 mm / 7/64"	3.2 mm / 1/8"	3.6 mm / 9/64"	4.0 mm / 5/32"	4.8 mm / 3/16"
9"	Single Trocar	Smooth	1620-509	1624-509	1628-509	1632-509	1636-509	1640-509	1648-509
		Threaded	1620-509T	1624-509T	1628-509T	1632-509T	1636-509T	1640-509T	1648-509T
	Double Trocar	Smooth	1620-109	1624-109	1628-109	1632-109	1636-109	1640-109	1648-109
		Threaded	1620-109T	1624-109T	1628-109T	1632-109T	1636-109T	1640-109T	1648-109T
	Single Diamond	Smooth	1620-609	1624-609	1628-609	1632-609	1636-609	1640-609	1648-609
		Threaded	1620-609T	1624-609T	1628-609T	1632-609T	1636-609T	1640-609T	1648-609T
	Double Diamond	Smooth	1620-709	1624-709	1628-709	1632-709	1636-709	1640-709	1648-709
		Threaded	1620-709T	1624-709T	1628-709T	1632-709T	1636-709T	1640-709T	1648-709T

K-Wire + Pin Protectors

Molded thermoplastic, protection from sharp points, and sold in sterile 4-packs.

For K-Wires	Wire Diameter			
		0.7 mm / .028"	0.9 mm / .035"	1.1 mm / .045"
Color	1601-028 Yellow	1601-035 Blue	1601-045 White	1601-062 Green

For Steinmann Pins	Wire Diameter						
		2.0 mm / 5/64"	2.4 mm / 3/32"	2.8 mm / 7/64"	3.2 mm / 1/8"	3.6 mm / 9/64"	4.0 mm / 5/32"
Color	1601-564 Pink	1601-332 Gray	1601-764 Tan	1601-180 Lavendar	1601-964 Brown	1601-532 Navy Blue	1601-316 Orange




TWIST DRILLS + TAPS

Standard Orthopaedic Twist Drills

MicroAire® Jacobs® Drill Couplers



Also fits all other standard Jacobs®-style Drill Couplers (Hall®, Stryker®, Synthes®, Aesculap®, DeSouter®, Brasseler®, etc.)

To order non-sterile, add "NS" to the end of the product number (e.g. 8054-XXXNS)

Type	Diameter (mm)	Length (mm)	MicroAire Part #	Replaces Zimmer®	
MicroAire Standard Twist Drills	1.6	127	8054-010	256-01-21	
	2.0		8054-011	256-01-22	
	2.4		8054-012	256-01-23	
	2.8		8054-013	256-01-24	
	3.2		8054-014	256-01-25	
	3.6	8054-015	256-01-26		
	4.0	127	8054-016	256-01-27	
	4.5		8054-017	256-01-28	
	4.8		8054-018	256-01-29	
	6.4		8054-019		
ECT® Twist Drills*	2.0	127	8054-020	2318-20	
	2.8		8054-021	2318-27	
	3.2		8054-022	2318-32	
	3.6		8054-023	2318-35	
	4.5		8054-024	2318-45	

*ECT® European Compression Technique



Small Power Instrument Twist Drills

MicroAire® Wire Driver		Models 1620, 1625, 1925, 1995 and 2600 with wire guide	Wire guide required (not included). Sold individually. Sterile or non-sterile; to order non-sterile, add "NS" to the end of the product number (e.g. 8051-XXXNS).
Diameter (mm)	Length (mm)	MicroAire Part #	
2.0	65	8051-120	
2.7	79	8051-127	
Wire Guide for Drills Sold in packs of 6 Non-sterile only		1600-012NS	

Standard Twist Drills with 2.34 mm Dental Bur Shank

May be used in standard MicroAire® and Linvatec® Micro Drills

Sold individually. Sterile or non-sterile; to order non-sterile, add "NS" to the end of the product number (e.g. 8051-XXXNS)

Diameter (mm)	Length (mm)	MicroAire Part #	 CAUTION: Do not operate above 10,000 RPM. Do not use in high-speed drill.
1.1	49	8051-011	
1.3	49	8051-013	
1.5	49	8051-015	
1.8	49	8051-018	
2.0	65	8051-020	
2.2	49	8051-021	
2.7	79	8051-027	
3.2	79	8051-032	
3.5	79	8051-035	